- the entire range of musical notes...



## CD 3

## The next generation, the new King, the GamuT CD 3!

After years of dedicated work and commitment to replace and refine one of the finest CD players in the world, the CDI, we proudly present the highly improved successor - the long awaited CD 3.

Creating a better CD player than the CDI has been a demanding task. It involved a complete redesign of the layout and the components used in the player to improve the electronic and mechanical stability. The result has been a state of the art CD player with a sound quality second to none.

The heart of the CD 3 is our nonmagnetic stainless steel inner chassis which holds the rubber suspended mechanism and the digital output board. Located in the centre of the player, the stainless steel inner chassis divides the interior space into three separate cabinets. This isolates the very heavy power supply and its associated heavy currents from the delicate signals being handled by the digital to analogue conversion and amplification located on the other side of the inner chassis.

The power supplies for the digital and analogue sections use two separate high quality toroidal power transformers to assure maximum stability, the lowest possible interference and a better separation between the two sections. To further ensure voltage stability the design of the digital to analogue board was made to incorporate special ultra low noise components. These changes ensure not only a better sounding CD player, but also one with increased stability and reliability.

The CD 3's digital to analogue conversion is built from the best components available today.

A 24 bit 192 kHz asynchronous sample rate converter was chosen to generate the up sampled signal for the 24 Bit Burr Brown PCM 1792 Converter. Special care was then taken to ensure the best possible analogue

amplification.

Great technical specifications do not on their own guarantee great sound. However, in the case of the CD 3 we are sure you will find it hard to believe not only the amount of detail, but also how well musicality is retrieved from your beloved records - even the ones you know so well. Never has realism been so close. Try the CD 3, get the GamuT experience.

## Listen and be convinced!

Technical specifications CD 3:

Output level:	4.35Vrms Balanced 2.15Vrms Unbalanced
Signal to noise ratio:	124dB Balanced 112dB Unbalanced
Noise level:	<5uV Balanced <10uV Unbalanced
THD+N:	<0.0009%
D/A converter:	24-Bit, 192kHz upsampling
Output impedances:	Balanced output 150 Ohm Unbalanced output 75 Ohm Digital output 75 Ohm
Mains voltages ranges:	230V AC / 115V AC
Idle power consumption:	20 Watts
Dimensions:	W 430 mm, D 420 mm, H III mm
Shipping weight:	15kg

Specifications subject to change without notice.









Oesterled 28 A · DK 4300 Holbaek, Denmark Phone Int. +45 70 20 22 68 · Fax Int. +45 59 43 97 26 E-mail: info@gamutaudio.com · www.gamutaudio.com