

elipson® | Prestige Facet II 14C

ENCEINTE CENTRALE - 2 VOIES - BASS-REFLEX LAMINAIRE



L'Elipson Prestige Facet II 14C est l'enceinte centrale idéale pour les installations home-cinéma de haute volée.

Cette centrale 2 voies intègre deux haut-parleurs de 170 mm et un tweeter de 25 mm, offrant une restitution vocale précise, dynamique et articulée.

Grâce à ses composants audiophiles et à son coffret repensé, elle s'impose comme la référence pour accompagner les colonnes de la série Facet II dans une configuration immersive et cohérente.





TECHNIQUE

Type Enceinte centrale - 2 voies Bass-reflex laminaire	Filtre répartiteur- Fc 3000 Hz - 18 dB / 18 dB
Puissance 150 W RMS	Impédance nominale 6 Ω
Amplification recommandée 40 - 200 W	Impédance minimale 4,5 Ω @ 180 Hz
Haut-parleurs Tweeter : 25 mm Grave-médiums : 2 x 170mm	Fréquence d'accord bass-reflex 57 Hz
Réponse en fréquence (±3dB) 43 Hz - 25 kHz	Bornier Argentés pour bi-câblage ou bi-amplification
Sensibilité 93dB / 1W / 1m	

DIMENSIONS
POIDS

Dimensions L600 x H207 x P250 mm	Poids 12,7 kg
--	-------------------------

PACKAGING

Packaging dimensions L720 X H320 x P370 mm	Poids brut 14,3 kg
--	------------------------------

FINITIONS
-
CODES
PRODUITS

	Finition Noir mat	SKU ELIPF214CMBK	EAN 3700795194485
	Finition Blanc mat	SKU ELIPF214CMWT	EAN 3700795194492
	Finitions Noir mat - Noyer	SKU ELIPF214CWNBK	EAN 3700795194508

elipson® | Prestige Facet II 14C

CENTRE LOUDSPEAKER - 2 WAY - LAMINAR BASS-REFLEX



The Elipson Prestige Facet II 14C is the ideal centre loudspeaker for high quality home cinema installations.

This 2-way centre loudspeaker incorporates two 7" drivers and a 1" tweeter, providing precise, dynamic and articulate vocal reproduction.

Thanks to its audiophile-grade components and its redesigned cabinet, it is the reference for accompanying the Facet II series floor-standing loudspeakers in an immersive, coherent configuration.





TECHNICAL

Type Centre loudspeaker - 2 way Laminar bass-reflex	Crossover 3000 Hz - 18 dB / 18 dB
Power 150 W RMS	Nominal impedance 6 Ω
Power amplifier 40 - 200 W	Minimum Impedance 4,5 Ω @ 180 Hz
Drive-Units Tweeter : 1" Mid-woofers : 2 x 7"	Tuned bass-reflex frequency 57 Hz
Frequency response (±3dB) 43 Hz - 25 kHz	Terminals Silver plated for bi-wiring or bi-amplification
Sensitivity 93dB / 1W / 1m	

DIMENSIONS
WEIGHTS

Dimensions W600 x H207 x D250 mm	Weight 12,7 kg
--	--------------------------

PACKAGING

Packaging dimensions W720 x H320 x D370 mm	Gross weight 14,3 kg
--	--------------------------------

FINISHES
-
PRODUCTS
CODES

	Finish Black matt	SKU ELIPF214CMBK	EAN 3700795194485
	Finish White matt	SKU ELIPF214CMWT	EAN 3700795194492
	Finishes Black matt - Walnut	SKU ELIPF214CWNBK	EAN 3700795194508