

Exposure 3010 S2 Pre amplifier (MM/MC phono card optional)

EX PRE 3010S

NZ\$1,595.00 (incl. GST)



"Exposure's 'Proudly Made in England by Music Lovers' tagline isn't just marketing BS. It's clear that the people behind these products know what music sounds like and are able to design components that bring music's emotional and intellectual power alive in a way that makes both standouts in their price class. The various combinations make listening to music so intensely involving that it borders on an addiction",Wayne Garcia, The Absolute Sound,

Features

Large custom made toroidal power transformer and smoothing capacitors for power supply Plug in MM or MC phono stage available, all discrete transistor audio stages 6 line inputs or 5 plus optional phono card, 2 main out (RCA) and 1 tape output High quality relays used for input source selection Full remote control of input selector, volume and mute Audio output stages utilising discrete transistor class A output buffer High quality all aluminium case work

Specifications

- Gain (at 1KHz) : +18dB
- Sensitivity : 250mV
- Maximum output : >10V RMS
- Frequency response : -3dB at 1Hz and 56KHz, ref. 1KHz, max volume
- Total Harmonic Distortion : <0.01% @ 1.6V RMS output, 1KHz
- Signal to Noise ratio : >96dB, A weighted, ref. 1.6V RMS output, 1KHz
- Channel Separation : >60dB 20Hz to 20KHz (Typically > 85dB@ 1KHz)
- Outputs : 2 pairs RCA, pre amp output, 1 pair for tape output
- Mains Supply : 110/120V or 220/240V, 50/60Hz (factory set)
- Power Consumption : <25VA
- Dimensions - H x W x D : 90mm x 440mm x 300mm
- Nett Weight (unpacked) : 7kg
- Gross Weight (packed) : 9kg

Link

<http://www.audioreference.co.nz/product/exposure-3010-s2-pre-amplifier-mmmc-phono-card-optional>